



TYPE III BARRICADE DETAIL

NTS

NOTES:

1. 4-INCH BY 4-INCH BY 8-FOOT POSTS SHALL BE PRESSURE TREATED LUMBER, PRIMED AND PAINTED WHITE.
2. RAILS SHALL BE PLASTIC, 1-INCH THICK BY 8-INCHES WIDE, ORANGE ON WHITE, WITH STRIPES FACTORY APPLIED, ENGINEER GRADE AS SUPPLIED BY TRAFFIC SAFETY SUPPLY.
3. LENGTH OF BARRICADE SHALL BE OF A LENGTH THAT WILL PHYSICALLY RESTRICT ACCESS BY MOTORIZED VEHICLES.
4. STRIPES SHALL ALTERNATE ORANGE AND WHITE, AND SLOPE DOWNWARD TO THE LEFT AT AN ANGLE OF 45°.
5. BARRICADE RAILS SHALL BE REFLECTORIZED.
6. BASE OF WOOD POST SHALL HAVE DRILLED HOLES OR OTHER BREAK-AWAY TYPE DESIGN AT 6 INCH MAXIMUM HEIGHT ABOVE FINISHED GRADE.
7. ALL MARKINGS SHALL COMPLY WITH M.U.T.C.D. STANDARDS.
8. ALL CONSTRUCTION AND MATERIALS SHALL MEET THE SPECIFICATIONS AND BE APPROVED BY THE CITY OF EPHRATA.
9. USE WSDOT STANDARD DETAIL PLAN H-2 FOR TEMPORARY TYPE III BARRICADE

**TO BE USED ONLY AS REQUIRED
OR APPROVED BY THE EPHRATA
PUBLIC WORKS DIRECTOR.**

**BARRICADE FOR TEMPORARY
NO-OUTLET STREET**

EPHRATA PUBLIC WORKS DEPARTMENT

CITY OF EPHRATA

DRAWN _____
CHECK _____
SCALE NTS
DATE 10/03/08



GRANT COUNTY

WASHINGTON

A-13

DATE	REVISION	BY